

Contact probes for L.V. tester

To be used only with MS-911/2 tester.

For overhead lines

Contact antennas serve as suspension hooks.

Marked with standard colours: black and red.

Total length: 1.25 m.

MS-8014 2 probes, in bag 50 x 130 x 1,300 mm - 0.40 kg



To be used only with MS-911/2 tester.

For installations

Round tip contact. Total length: 0.50 m.

MS-8013 2 probes, in bag 50 x 150 x 470 mm - 0.750 kg



Voltage take-off punch

The voltage take-off punch is able to make an insulating piercing on a low voltage wire to plug a measurement device.

Fit with pin or safety test probe with 4 mm diameter.

Reference	Capacity (Ø mm)	Weight (kg)
MS-62	5.6 - 14.4	0.015
MS-63	12 - 31	0.05



POINTEST™ Safety test probes for voltage detectors

Safety test probe for voltage detector use only.

4 mm retractable shrouded plug, 4 mm standard socket or 1,20 m double sheathed lead, Probe 26 mm length, 1 000 V A.C or D.C, IP2X.

IEC 61010-2-031



CX-35811 Green safety test probe 1.20 m lead

CX-45211 Brown safety test probe 1.20 m lead

CX-45511 Black safety test probe 1.20 m lead

CX-45411 Yellow safety test probe 1.20 m lead



Safety crocodile clamps

Crocodile clamps.

Fully insulated crocodile clamps with large jaw opening: 20 mm.

IEC 61010-2-031



CX-01222 5 brown crocodile clamps

CX-01422 5 yellow crocodile clamps

CX-01822 5 green crocodile clamps

DX-02006 2 crocodile clamps - black and red

