

# **Empower Drives And Automation Sdn. Bhd.**



## **FEM LV Motor**

Brand FEM

#### Description

The new series of FRANDER ELEKTRIM MOTOR, now written in short form FEM, is robust in design and construction to meet the ever increasing demand in quality for all standard industries drives. The output range from 1.1kW to 90kW now manufactured to the high efficiency meeting the requirement to the EUROPE standard of efficiency level. The word IE1 & IE2 appearing on the nameplate shall designated to its performance.

## Catalogue Download:

https://fem-gearmotor.com.my/attachments/3755/download

# **Gearbox - Hollow Shaft & Flange**

Brand	FEM
Holical Poyol Coarbox	12 Cizoc

## Description

FEM bevel gearbox consisted of double stage and triple stage reduction to suit varies kind of application.

It has a higher efficiency on power transmission and are able to have higher input and output rating.

- Twelve Sizes : 37,47,57,67,77,87,97,107,127, 157,167,187
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 200kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor





# **Gearbox - Solid Shaft and Flange**

Brand	FEM
Helical Bevel Gearbox	12 Sizes

## Description

FEM bevel gearbox consisted of double stage and triple stage reduction to suit varies kind of application.

It has a higher efficiency on power transmission and are able to have higher input and output rating.

- Twelve Sizes : 37,47,57,67,77,87,97,107,127, 157,167,187
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 200kW

- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor

# Gearbox - Solid Output & IEC Adaptor

Brand	FEM
Helical Bevel Gearbox	12 Sizes

### Description

FEM bevel gearbox consisted of double stage and triple stage reduction to suit varies kind of application.

It has a higher efficiency on power transmission and are able to have higher input and output rating.

- Twelve Sizes: 37,47,57,67,77,87,97,107,127, 157,167,187
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 200kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor





# **Gearbox - Output & Input Solid Shaft**

Brand	FEM
Helical Bevel Gearbox	12 Sizes

#### Description

FEM bevel gearbox consisted of double stage and triple stage reduction to suit varies kind of application.

It has a higher efficiency on power transmission and are able to have higher input and output rating.

- Twelve Sizes: 37,47,57,67,77,87,97,107,127, 157,167,187
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 200kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor

# **Gearbox - Output Flange & Shaft**

Brand	FEM
Helical Worm Gearbox	7 Sizes

## Description

FEM Worm gearbox consisted of double stage and triple stage reduction to suit varies kind of application.

Right angle output and it compact size is suitable on close space environment installation.

- Seven Sizes : 37,47,57,67,77,87,97
- Output Shafts Solid, Hollow with Key/Shrink Disc
- $\bullet$  Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 22kW
- Nominal torque rating up to 4000Nm
- IEC Adaptor that suit any IEC Motor





# Gearbox - Hollow Shaft with C Flange

Brand	FEM
Helical Worm Gearbox	7 Sizes

### Description

FEM Worm gearbox consisted of double stage and triple stage reduction to suit varies kind of application.

Right angle output and it compact size is suitable on close space environment installation.

- Seven Sizes: 37,47,57,67,77,87,97
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 22kW
- Nominal torque rating up to 4000Nm
- IEC Adaptor that suit any IEC Motor

# **Gearbox - Solid Output Shaft**

Brand	FEM
Helical Worm Gearbox	7 Sizes

### Description

FEM Worm gearbox consisted of double stage and triple stage reduction to suit varies kind of application.

Right angle output and it compact size is suitable on close space environment installation.

- Seven Sizes : 37,47,57,67,77,87,97
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 22kW
- Nominal torque rating up to 4000Nm
- IEC Adaptor that suit any IEC Motor





# **Gearbox - Hollow Shaft & Flange**

Brand	FEM
Helical Worm Gearbox	7 Sizes

## Description

FEM Worm gearbox consisted of double stage and triple stage reduction to suit varies kind of application.

Right angle output and it compact size is suitable on close space environment installation.

- Seven Sizes: 37,47,57,67,77,87,97
- $\bullet$  Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 22kW
- Nominal torque rating up to 4000Nm
- IEC Adaptor that suit any IEC Motor

Brand FEM
Parallel Shaft Gearbox 12 Sizes

#### Description

FEM parallel shaft mount gearbox consisted of double stage and triple stage reduction to suit varies kind of <a href="mailto:application.lt">application.lt</a> has varies types of configuration to accommodate different type of mounting requirement.

- Twelve Sizes: 37,47,57,67,77,87,97,107,127, 157,167,177
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 250kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor





# **Gearbox - Output & Input Solid Shaft**

Brand	FEM
Parallel Shaft Gearbox	12 Sizes

## Description

FEM parallel shaft mount gearbox consisted of double stage and triple stage reduction to suit varies kind of <a href="mailto:application.lt">application.lt</a> has varies types of configuration to accommodate different type of mounting requirement.

- Twelve Sizes : 37,47,57,67,77,87,97,107,127, 157,167,177
- $\bullet$  Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 250kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor

# Gearbox - Output Shaft & IEC Adaptor

Brand	FEM
Parallel Shaft Gearbox	12 Sizes

### Description

FEM parallel shaft mount gearbox consisted of double stage and triple stage reduction to suit varies kind of <u>application.lt</u> has varies types of configuration to accommodate different type of mounting requirement.

- Twelve Sizes: 37,47,57,67,77,87,97,107,127, 157,167,177
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 250kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor





# Gearbox - Hollow Shaft & C Flange

Brand	FEM
Parallel Shaft Gearbox	12 Sizes

#### Description

FEM parallel shaft mount gearbox consisted of double stage and triple stage reduction to suit varies kind of <a href="mailto:application.lt">application.lt</a> has varies types of configuration to accommodate different type of mounting requirement.

- Twelve Sizes: 37,47,57,67,77,87,97,107,127, 157,167,177
- Output Shafts Solid, Hollow with Key/Shrink Disc
- Output Flanges B14 & B5, Torque Arm
- Mounting B3, B5, V1
- Input rating up to 250kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor

# **Gearbox - Foot Mount**

Brand	FEMFEM
Single Stage	13 Sizes
Gearbox	

### Description

FEM Inline Helical Gear Reducer

FEM inline gearbox consisted of single stage, double stage and up to triple stage reduction to suit varies kind of application. It also can combined with other series of FEM

that can achieve greater required ratio.

gearbox to make a tandem gearbox

- Thirteen Sizes : 37,47,57,67,77,87,97,107,137,147,167,177,
- Output Shafts Metric
- Output Flanges B14 & B5
- Mounting B3, B5, B35, V1
- Input rating up to 250kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor
- All gearboxes are filled with VG220 mineral oil prior to shipping





# **Gearbox - Tandem Configuration**

Brand	FEM
Tandem Gearbox	14 Sizes

## Description

FEM Inline Helical Gear Reducer

FEM inline gearbox consisted of single stage, double stage and up to triple stage reduction to suit varies kind of application. It also can combined with other series of FEM gearbox to make a tandem gearbox that can achieve greater required ratio.

- Thirteen Sizes : 37,47,57,67,77,87,97,107,137,147,167,177, 187
- Output Shafts Metric
- Output Flanges B14 & B5

- Mounting B3, B5, B35, V1
- Input rating up to 250kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor
- All gearboxes are filled with VG220 mineral oil prior to shipping

# **Gearbox - IEC Adaptor**

Brand	FEM
Inline Helical Gearbox	13 Sizes

## Description

FEM Inline Helical Gear Reducer

FEM inline gearbox consisted of single stage, double stage and up to triple stage reduction to suit varies

kind of application. It also can combined with other series of FEM gearbox to make a tandem gearbox  $\,$ 

that can achieve greater required ratio.

- Thirteen Sizes : 37,47,57,67,77,87,97,107,137,147,167,177,
- Output Shafts Metric
- Output Flanges B14 & B5
- Mounting B3, B5, B35, V1
- Input rating up to 250kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor
- All gearboxes are filled with VG220 mineral oil prior to shipping





# **Gearbox - Output & Input Shaft**

Brand	FEM
Inline Helical Gearbox	L3 Sizes

## Description

FEM Inline Helical Gear Reducer

FEM inline gearbox consisted of single stage, double stage and up to triple stage reduction to suit varies kind of application. It also can combined with other series of FEM gearbox to make a tandem gearbox that can achieve greater required ratio.

- Thirteen Sizes : 37,47,57,67,77,87,97,107,137,147,167,177, 187
- Output Shafts Metric
- Output Flanges B14 & B5
- Mounting B3, B5, B35, V1
- Input rating up to 250kW
- Nominal torque rating up to 50000Nm
- IEC Adaptor that suit any IEC Motor
- All gearboxes are filled with VG220 mineral oil prior to shipping

## **FEM Gear Unit for Palm Oil Mill**

Brand FEM

## Description

The renown FEM gear unit is design for higher output torque and long lasting. It has the similar dimension that are interchangeable with major brand in the palm oil mill market.

It is suitable for the equipment such as screw press, digester and kernal expeller.

















# **Slip-Ring Motors**

Brand FEM

### Description

SLIP-RING MOTORS

• SLIP-RING FOR CONTINUOUS DUTY

## INTRODUCTION

The three phase slip ring asynchronous motor is designed to achieve higher starting torque with lower starting current. This is particularly achievable in area where there is limited power supply or when electrical generator is in used instead of main power. It is commonly used in conjunction of starting for various equipments such as stone crusher in the quarrying industries, ID fan for boiler, compressor, pre-breaker machine for the rubber industries, bucket elevator and others rotating machines that require high starting torque with limiting starting current due to circumstances and environmental constrains.

# **Empower Drives And Automation Sdn. Bhd.**

Lot 7792, Kampung Baru Subang, Seksyen U9, 40150, Shah Alam, Selangor, Malaysia

Tel	03-7846 9196
Fax	03-7846 9180
Mobile	+6012 304 3316
Phone	
E-Mail	enquiry@empowercorp.com.my
E-Mail	choong@empowercorp.com.my
E-Mail	sharon@empowercorp.com.my
E-Mail	kee@empowercorp.com.my
Website	www.empowercorp.com.my
Website	www.fem-gearmotor.com.my

WhatsApp.....https://wa.me/0123043316

Empower	Empower Drives And Automation Sdn. Bhd.								